

## T-3530 / T-3560 FERRITE ISOLATORS

Telewave Single and Dual Ferrite Isolators prevent intermodulation, and protect transmitters from high VSWR or mistuned filtering devices by providing a constant 50 ohm impedance. All Telewave isolators are manufactured and tested in our own plant to the highest quality standards. These isolators handle up to 150 watts of power, with several different load options. All Telewave isolators include one or two removeable 35 watt loads in the basic configuration. Typical tuning range is up to  $\pm 5$  MHz from the original center frequency, and typical isolation is 35 dB for single, and 70 dB for dual.

**NOTE:** Isolators have limited bandwidth and tuning range. Each isolator is manufactured for a specific range and tuned to a specific frequency. Please specify the exact desired operating frequency and special load requirements with the order.

### BENEFITS

Under adverse conditions, the isolator performs several critical functions:

#### Broken Antenna, Damaged Cable, High VSWR

All of these conditions will cause large amounts of power to be reflected down the transmission line toward the transmitter. The circulatory property of the isolator will direct this energy to the load port, and protect the transmitter. The load on the isolator must be capable of handling full transmitter power. Age, water invasion, and incorrect cable length will also cause impedance changes. The tuned ports of the isolator provide a constant 50 ohm impedance for the transmitter to avoid overheating and oscillation.



T-3530 SINGLE ISOLATOR



T-3560 DUAL ISOLATOR

#### Intermodulation

When in-band or out-of-band RF energy from a strong nearby signal source couples into the transmitter, mixing with the primary frequency often occurs, resulting in the radiation of new, undesired signals. The isolator antenna port will reflect out-of-band energy back to the antenna. in-band energy enters the isolator, and is directed to the load. No energy from nearby transmitters enters the primary transmitter, and intermodulation is typically eliminated.

SPECIFICATIONS			T-3530	T-3560
Frequency band	300-400 MHz	Isolator type	Single	Dual
Tuning range (typ.)	$\pm 5$ MHz	Isolation (typ. / min)	35 dB / 30 dB	70 dB / 60 dB
Input power	150 watts	Insertion loss (typ.)	0.4 dB	0.8 dB
VSWR (typ.)	1.25:1	Load(s) included	(1) 35W	(2) 35 W
Impedance	50 ohms	Dimensions (HWD) in.	2 x 3 x 3	2 x 5.5 x 2.75
Connectors	N Female	(Height incl. loads) cm	5.1 x 7.6 x 7.6	5.1 x 14 x 7
Temperature range	-30°C to +60°C	Weight lb. (kg)	3 (1.4)	6 (2.7)