

## ANT150Y7-WR YAGI ANTENNA 5 dBd




The Telewave ANT150Y7-WR is a high performance directional antenna, designed especially for point to point as well as point to multipoint applications. This antenna produces 5 dBd forward gain with an excellent front-to-back ratio, and solid aluminum elements with 360° welds prevent intermodulation and provide exceptional strength.

Each antenna is completely protected with our high-tech Txylan™ coating, which provides icing resistance and environmental protection from corrosive gases,


ultraviolet radiation, salt spray, acid rain and wind blown abrasives such as desert sand. The feed line is protected within the boom, and the radiating element connection is completely sealed against ice and other environmental hazards with a tough, RF-transparent radome.

The ANT150Y7-WR includes a welded vertical plate and mast clamp set. A horizontal plate is optional. The clamp set secures the antenna to a vertical mast or tower support from 1.5" - 3.5" O.D.

ANT150Y7-WR at 156 MHz




E-Plane  
Gain: 5.1 dBd



H-Plane  
Gain: 5.1 dBd

TYPICAL VSWR RESPONSE



SPECIFICATIONS			
Frequency (continuous)	148-174 MHz	Elements	3
Gain (typ)	5 dBd	Dimensions (L x H)	38 x 40.5 in.
Power rating (typ)	500 watts	Antenna weight	16 lb.
Impedance / VSWR	50 ohms / 1.5:1 (max)	Shipping weight	19 lb.
Front to back ratio (min)	20 dB	Wind rating / with 0.5" ice	150 / 125 MPH
Beamwidth V / H	64° / 114°	Exposed area (flat plate equiv.)	1.0 ft. <sup>2</sup>
Pattern / Polarization	Directional / Vertical	Lateral thrust at 100 MPH	41 lb.
Termination	N Female or 7-16 DIN (opt)	(40 psf - flat plate equiv.)	