


ANT380Y7-WR

YAGI ANTENNA 7 dBd


380 – 400 MHz



ANT380Y7-WR at 390 MHz



E-Plane
Gain: 7.15 dBd



Gain: 7.24 dBd

The Telewave.io ANT380Y7-WR is such as desert sand. The feed line is a high performance directional antenna, designed especially for point to point as well as point to multipoint applications. This antenna produces 7 dBd forward gain with an excellent front-to-back ratio. Solid aluminum elements with 360° welds prevent intermodulation and provide exceptional strength.

Each antenna is completely protected with our high-tech Txylan™ coating, which provides icing resistance and environmental protection from corrosive gases, ultraviolet radiation, salt spray, acid rain and wind blown abrasives

is protected within the boom, and the radiating element is completely sealed against ice and other hazards with a tough, RF-transparent radome.

The ANT380Y7-WR includes a welded vertical plate and mast clamp set. A horizontal plate is optional. The clamp set secures the antenna to a vertical mast or tower support from 1.5" - 3.5" O.D. For installations on angled supports, the "U" mount allows mounting to virtually all angled supports up to 3.5" O.D.

SPECIFICATIONS			
Frequency (continuous)	380-400 MHz	Elements	4
Gain (typ)	7 dBd	Dimensions (L x H)	34x 18 in.
Power rating (typ)	500 watts	Antenna weight	8.5 lb.
Impedance/ VSWR	50 ohms / 1.5:1 (max)	Shipping weight	11 lb.
Front to back ratio (min)	16 dB	Wind rating / with 0.5" ice	150 / 125 MPH
Beamwidth V / H	60° / 105°	Exposed area (flat plate equiv.)	0.625 ft. ²
Pattern / Polarization	Directional/ Vertical	Lateral thrust at 100 MPH	25 lb.
Termination	N Female or 7-16 DIN (opt)	(40 psf - flat plate equiv.)	